

**VIDEOFLEX®**  
*Cad Cut® material*

<b>Description</b>	Cad Cut® material suitable for 100% cotton, 100% polyester, poly-cotton blends and most synthetic fabrics (except nylon). Polyester backing.
<b>Tips</b>	<b>Special colours on request – Minimum quantity 300 m. (450 sqm.)</b>  <b>Oeko-Tex Standard 100, Class II (products in direct contact to skin) compliant</b>  We highly recommend application and washing test.
<b>Application instructions</b>	1)Cut in REVERSE 2)Heat apply with its own polyester backing 3)Remove backing when <b>cold</b>  Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:
<b>Temperature:</b>	150°C
<b>Time:</b>	10 – 15 sec.
<b>Pressure:</b>	medium
<b>Washable to:</b>	80°C Max.

**SIZES AND COLOURS**

<b>ROLLS</b>	width 1,50 m.	length 30 m.
	width 0,50 m.	length 30 m.
<b>COLOURS</b>	white, black, royal blue, navy blue, red, yellow, green, orange, pink, light blue, brown, gold, silver, burgundy, violet	
<b>DAY-GLO</b>	yellow, blue, orange, pink, green	

*Last updating: January 2005*